

## Technical data sheets BMW Motorrad

Date: 30.08.2021  
Status: approved

MY2022

### R nineT Urban G/S

#### Engine

Type	Air/oil-cooled flat twin ('Boxer') 4-stroke engine, two camshafts and four radially aligned valves per cylinder, central counterbalancer shaft
Bore / stroke	101 mm x 73 mm
Capacity	1,170 cc
Rated output	80 kW (109 hp) at 7,250 rpm
Max. torque	116 Nm at 6,000 rpm
Compression ratio	12.0 : 1
Mixture control	Electronic intake pipe injection / digital engine management with overrun cutoff, twin-spark ignition
Emission control	Controlled 3-way catalytic converter, exhaust emission standards EU-5

#### Performance / fuel consumption

Maximum speed	over 200 km/h
Fuel consumption per 100 km based on WMTC	5.1 l
CO <sub>2</sub> emission based on WMTC	119 g/km
Fuel type	Unleaded super(premium), octane number 95-98 (RON) (rated output at 98 RON)

#### Electrical system

Alternator	three-phase alternator 720 W
Battery	12 V / 12 Ah, maintenance-free

#### Power transmission

Clutch	Single dry plate clutch, hydraulically operated
Gearbox	Claw-shifted six-speed transmission with helical-cut splines
Drive	Shaft drive

#### Chassis / brakes

Frame	three-part frame concept with front frame and two-part rear frame, load-bearing engine-gearbox unit, rear-set frame removeable for one-up riding
Front wheel location / suspension	Telescopic forks, 43 mm fixed-tube diameter
Rear wheel location / suspension	Cast aluminium single swinging arm with BMW Motorrad Paralever; central spring strut, spring preload fully adjustable by hook wrench, adjustable rebound-stage damping
Suspension travel, front / rear	125 mm / 140 mm
Wheelbase	1,527 mm
Castor	110.6 mm
Steering head angle	61.5°
Wheels	Cast wheels
Rim, front	3.00 x 19"
Rim, rear	4.50 x 17"
Tyre, front	120/70 R 19
Tyre, rear	170/60 R 17
Brake, front	Twin-disc brakes, diameter 320 mm, 4-piston callipers
Brake, rear	Single disc brake, diameter 265 mm, double-piston floating caliper
ABS	BMW Motorrad ABS

#### Dimensions / weights

Seat height	850 mm
Inner leg curve	1,890 mm
Usable tank volume	17 L
Reserve	app. 3.5 L
Length	2,175 mm
Height (incl. mirrors)	1,330 mm
Width (incl. hand levers)	865 mm
Unladen weight, road ready, fully fuelled 1)	223 kg
Permitted total weight	430 kg
Payload (with standard equipment)	207 kg

#### Equipment (in parts)

Standard equipment	LED headlight with daytime running light (where homologated), speed indicator with on-board computer content, ASC, riding modes rain & road, drive train and final drive black, USB charging socket
Optional equipment (OE)	Comfort package incl. Riding modes PRO (incl. Riding mode DIRT), cruise control and heated grips, Aluminum Fuel Tank, paint sets, Cross spoked wheels I & II, Option 719 billet packages I & II, Off Road tires
Optional accessories (OA)	Rev. counter with on-board computer, Tail short, Tail Tracker, function integrated turning signals, cylinder head covers 2V-Style, and more well tried and tested parts known from R nineT derivatives

#### Technical data relate to the unladen weight (DIN)

1) According to guideline VO (EU) 168/2013 with all fluids, with standard equipment and fuelled with at least 90% of usable tank volume.  
(only OE-USPs compared to competition)