Technical data sheets BMW Motorrad

10.08.2021 MY 2022 (0G43)

G 310 R

Engine Type Water-cooled, single-cylinder 4-stroke engine, four valves, two overhead camshafts and cam followers, wet sump lubrication

Bore / stroke 80 mm x 62.1 mm

Capacity 313 cc

25 kW (34 hp) at 9,250 rpm Rated output Max. torque 28 Nm at 7,500 rpm Compression ratio 10.9:1 Mixture control Electronic fuel injection

Closed-loop 3-way catalytic converter, emission standard EU-5 Emission control

Performance / fuel consum Maximum speed Fuel consumption per 100 km based on WMTC 3.51 CO₂ emission based on WMTC 80 g/km

Unleaded regular, minimum octane number 91 (RON)

Electrical system Alternator

Fuel type

three-phase alternator 308 W Battery 12 V / 8 Ah, maintenance-free

Multiplate clutch in oil bath, anti-hopping clutch, with self-reinforcement

Gearbox Constant mesh 6-speed gearbox integrated in crankcase Drive Endless X-ring chain with shock damping in rear wheel hub

Chassis / brakes

Front wheel location / suspension Upside down fork, Ø 41 mm

Rear wheel location / suspension Cast aluminium dual swing arm, central spring strut, spring pre-load adjustable

Suspension travel, front / rear 140 mm / 131 mm Wheelbase 1,380 mm 114 mm Castor 64.9° Steering head angle

Wheels Cast aluminium wheels

Rim, front 3.00 x 17" 4.00 x 17" Rim, rear Tyre, front 110/70 R 17 Tyre, rear 150/60 R 17

Brake, front Single disc, diameter 300 mm, 4-piston fixed caliper, radially bolted Single disc, diameter 240 mm, single-piston floating caliper Brake, rear

ABS BMW Motorrad ABS

ions / weights Seat height

785 mm (OA low seat 770 mm, OA high seat 800 mm) 1,760 mm (OA low seat 1,730 mm, OA high seat 1,790 mm) Inner leg curve

11,01 Usable tank volume Reserve approx. 1,0 l Length 2.005 mm Height (excl. mirrors) 1,080 mm Width (incl. mirrors) 849 mm Unladen weight, road ready, fully fuelled 1) 164 kg Permitted total weight 345 kg Payload (with standard equipment) 181 kg

Equipment (in parts)

Standard equipment BMW Motorrad ABS, ride by wire, stainless steel exhaust system, 100% LED head-,tail light and LED indicator, adjusable brake- and clutch

Optional equipment (OE)

Optional accessories (OA) low seat, high seat, LED indicators, luggage rack, topcase "Light", topcase 30 I, heated grips, 12 V power outlet, USB charging socket

Technical data relate to the unladen weight (DIN)

1) According to guideline VO (EU) 168/2013 with all fluids, with standard equipment and fuelled with at least 90% of usable tank volume.