itand:	27.07.2021	МЈ 2022
itatus:	freigegeben	0F31; 0F33
		K 1600 GTL
ngine		
	Туре	Oil-/watercooled 4-stroke in-line 6-cylinder engine, two overhead camshafts, four valves per cylinder
	Bore / stroke	72 mm x 67,5 mm
	Capacity	1.649 cm ³
	Rated output	118 kW bei 6.750 1/min
	Max. torque	180 Nm bei 5.250 1/min
	Compression ratio	12,2 :1
	Mixture control	Electronic intake pipe injection
		digital engine management system: BMS-O with throttle-by-wire
	Emission control Emission standard	Closed-loop 3-way catalytic converter EU5
orform	ance / fuel consumption	
1101116	Maximum speed	over 200 km/h
	Fuel consumption per 100 km based on WMTC	5,9 l/100km
	CO2 emission based on WMTC	137 g/km
	Fuel type	Unleaded super (max. 15 % Ethanol, E15) RON 95 90 AKI
ectrica	l system	
	Alternator	three-phase alternator 700 W (nominal power)
	Battery	12 V / 16 Ah, maintenance-free
ower tra	ansmission	
	Clutch	Multiple-disc clutch in oil bath
	Gearbox	6-speed, helical, gearbox
	Drive	shaft drive
hassis /	brakes	
	Frame	Bridge-type frame, cast aluminium, load-bearing engine
	Front wheel location / suspension	BMW Motorrad Duolever; central spring strut
	Rear wheel location / suspension	Cast aluminium single-sided swing arm with BMW Motorrad Paralever; central spring strut
	Suspension travel, front / rear	115 mm / 135 mm
	Wheelbase, normal load with rider	1.618 mm
	Castor, normal load with rider	106,4 mm
	Steering head angle, unloaded	62,2°
	Wheels	Cast aluminium wheels
	Rim, front	3,50" × 17"
	Rim, rear	6,00" × 17"
	Tyre, front	120/70 ZR 17
	Tyre, rear	190/55 ZR 17
	Brake, front	Dual disc brake, diameter 320 mm, 4-piston fixed calipers
	Brake, rear ABS	Single disc brake, diameter 320 mm, double-piston caliper BMW Motorrad Integral ABS Pro (part-integral, slant-layer-optimized)
imensio	ons / weights Seat height	750 mm
	Inner leg curve	1.760 mm
	Usable tank volume	ca. 26,5 l
	Reserve	ca. 4
	Length (over Topcase)	2.489 mm
	Height (at windshield and topcase)	1.490 - 1.580 mm
	Width (incl. side cases)	1.000 mm
	Unladen weight, road ready, fully fuelled 1)	358 kg
	Permitted total weight	560 kg
	Payload (with standard equipment)	202 kg
uinme	nt (in parts)	
laihiue	Standard equipment	10,25 inch color TFT display with connectivity and integrated map-navigation (by BMW Motorrad connected app),
		charging storage for mobile phone (USB-C), fully LED headlight with light icon and adaptive cornering light, double to fanfare, 4 configurable favorit button cluster, DTC (dynamic traction control), 3 riding modes (RAIN, ROAD and
		DYNAMIC), MSR (engine brake control), Dynamic ESA next generation (elektronic suspension adjustment with autom- load leveling), HSC Pro (hill start control), RDC (tyre pressure control), heating grips, seat heating, side cases, topcase,
	Optional equipment (OE)	audio system (f.e. with DAB+, SAT-radio and sound-profiles) Keyless Ride, central locking system, gear shift assist pro, anti theft alarm, Option 719 wheels, LED auxiliary head lam ground-level lighting, engine protection guard, high seat, Option 719 seat, Option 719 classic forged wheels
	Optional accessories (OA)	armrest fpr passenger, liner for topcase and side case, tank bag, sport silencer, chrome parts, low windscreen

1) According to guideline VO (EU) 168/2013 with all fluids, with standard equipment and fuelled with at least 90% of usable tank volume.