## Technical data sheets BMW Motorrad

25.05.2018

MY 2019

## C 400 GT

Water-cooled single cylinder 4 stroke engine, 4 valves per cylinder, overhead camshaft with Type

rocker arm, wet sump lubrication Bore / stroke 80 mm x 69,6 mm

350 ccm Capacity

Rated output 25 kW (34 hp) at 7.500 rpm 35 Nm at 6.000 rpm Max. torque

Compression ratio 11,5:1

Mixture control / engine management BMS-E2 digital engine management

Emission control Closed-loop 3-way catalytic converter, emission standard EU-4

Performance / fuel consumption

139 km/h Fuel consumption per 100 km based on WMTC 3,511 CO<sub>2</sub> emission based on WMTC 81 g/km

Fuel type Unleaded super 95 (ROZ), E10 compatible

Electrical system

Alternator Three-phase generator 316 W Battery 12 V / 9 Ah, maintenance-free

500 Watt Starter

Clutch Centrifugal dry clutch Stepless CVT gearbox Secondary Drive Two step spur gearing

Chassis / brakes

Steel tube construction with aluminum die cast unit Frame

Front wheel location / suspension Telescopic front fork Ø 35 mm

Double Aluminum swingarm, Double spring struts, adjustable preload Rear wheel location / suspension

Suspension travel, front / rear 110 mm / 112 mm 1.565 mm Wheelbase Castor 81 mm Steering head angle 63.6°

Wheels Aluminum cast wheels

Rim, front 3.50 x 15" Rim, rear 4,25 x 14" Tyre, front 120/70 15 Tyre, rear 150/70 14

Double disc brake, rigid, diameter 265 mm, 4-piston calipers Brake, front

Brake, rear Single disc brake, diameter 265 mm, 1-piston floating caliper

ABS BMW Motorrad ABS

nensions / weights Seat height

775 mm Inner leg curve 1.760 mm Usable tank volume 12,81 Reserve 41 Length (over mark carrier) 2.210 mm Height (over windshield, at unladen weight (DIN)) 1.437 mm Width (incl. mirrors) 835 mm

Unladen weight, road ready, fully fuelled 1) 212 kg (dry weight 201 kg)

Permitted total weight 415 kg Payload (with standard equipment) 203 kg

Equipment (in parts)

Optional equipment (OE)

BMW Motorrad ABS, stainless steel exhaust system, LED headlight incl. LED daytime riding Standard equipment

light, LED tail light and turn indicators, Keyless ride, flex-case, ASC (Automatic Stability

Control), center stand

Comfort package (heated hand grips, heated seat)

Connectivity package (colour TFT display, multi-controller, associated apps)

Single OE (anti-theft alarm)

Optional accessories (OA)

Top case varients, liner for topcase, luggage carrier, windshield varients, seat 760 mm, scooter canopy, BMW navigator, Bracket for BMW Motorrad navigator/Smartphone, dual USB charger

Technical data relate to the unladen weight (DIN)

1) According to guideline VO (EU) 168/2013 with all fluids, with standard equipment and fuelled with at least 90% of usable tank volume.